



HEAT PUMPS *for Pools & Spas*



Best In Class!

Consistently heat your pool and extend your swimming season with our full line of heat pumps! The most efficient way to heat your pool or spa!

- 100% Pure, Commercial-Grade Titanium Heat Exchanger
- PRO Smart Control Panels Are the Most Innovative and Adaptable On the Market Today!
 - Self Diagnostic Codes, Determining Your Issue for You
 - Automatic Defrost Mode Allowing Heating In Outside Temperatures As Low As 38°
 - High Temperature Lock-Out Feature
 - Compatible With All Known Remote Systems
 - Override Any Time Clock To Maintain Desired Temperature
- Innovative Silent Series Product Design


The Features You Need!

	PRO1400HC	PRO1400	PRO1100	PRO800	ECO500	PRO500
Heat Exchanger Construction	TITANIUM	TITANIUM	TITANIUM	TITANIUM	TITANIUM	TITANIUM
Heating & Cooling Modes	Heat & Cool	Heat Only	Heat Only	Heat Only	Heat & Cool	Heat Only
Temperature Control	Digital	Digital	Digital	Digital	Digital	Digital
Ideal for Pools Up To: (Gallons)	40,000 gal	40,000 gal	28,000 gal	24,000 gal	16,000 gal	16,000 gal
Remote Compatibility	2 & 3-Wire	2 & 3-Wire	2 & 3-Wire	2 & 3-Wire	2-Wire	2 & 3-Wire
Performance Testing Results:						
	COP	5.8	5.8	6.0	6.5	5.1
*(80°F air, 80°F water, 80% RH)	BTU/hr	137,000	137,000	112,000	83,000	50,000
	COP	5.2	5.2	5.7	6.0	4.9
** (80°F air, 80°F water, 63% RH)	BTU/hr	125,000	125,000	107,000	79,000	43,000
	COP	4.0	4.0	4.0	4.0	3.5
** (50°F air, 80°F water, 63% RH)	BTU/hr	86,000	86,000	77,000	50,000	29,000
Voltage Required:	230/208 V	230/208 V	230/208 V	230/208 V	230/208 V	230/208 V
*Operating Current:	29 Amps	29 Amps	26 Amps	20 Amps	10 Amps	10 Amps
Recommended Circuit Breaker:	50 Amps	50 Amps	50 Amps	25 Amps	20 Amps	20 Amps
Maximum Circuit Breaker:	60 Amps	60 Amps	60 Amps	30 Amps	30 Amps	25 Amps
Refrigerant:	R410A	R410A	R410A	R410A	R410A	R410A
Minimum Water Flow Rate:	25 GPM	25 GPM	25 GPM	25 GPM	20 GPM	25 GPM
Maximum Water Flow Rate:	80 GPM	80 GPM	80 GPM	80 GPM	45 GPM	60 GPM
Dimensions:	W x D x H	35"x35"x43"	35"x35"x43"	35"x35"x39"	31"x31"x34"	17"x41"x28"
Net Weight:		295 lbs.	295 lbs.	285 lbs.	230 lbs.	170 lbs.
Shipping Weight:		315 lbs.	315 lbs.	305 lbs.	245 lbs.	209 lbs.

* Ratings outside scope of AHRI1160

** Ratings in accordance with AHRI1160

Save Up to 85% Over the Cost of Gas Heating Now!



877.278.2797 • F 888.610.3839
 cs@aquapro systems.com • www.aquapro systems.com