



Pool Wake Up!™ Operation Instructions For Spring Openings

It's as easy as Ready, Set, Go!



FROG Leap
Depth Charge™

READY:

Start by removing
contaminants to keep
water crystal clear



FROG Leap
Reveille™

SET:

Then set your
initial chlorine
level



FROG Leap
ALL-OUT™

GO:

Then prevent algae with
a 90-day algae
protection guarantee

(see website below for guarantee details)

1. FROG Leap Depth Charge™


After balancing the pool water and inserting a new FROG Leap Anti-Bac Mineral Pac into the FROG Leap or POOL FROG System, insert FROG Leap Depth Charge using steps 1 through 7.

Water Balance Guidelines

pH:	7.2 – 7.8
Total Alkalinity:	60 – 120 ppm
Calcium Hardness:	150 – 400
Total Dissolved Solids:	<1500
Stabilizer:	20 – 80 ppm
Free Chlorine:	0.5 – 1.0 ppm



1. With the circulation system off, set control dial to 0 and remove the cap to the FROG Leap or POOL FROG System.



2. Remove caps from FROG Leap Depth Charge with a pliers or other suitable tool.



3. Turn FROG Leap Depth Charge over so open ends face down and insert into the center of the FROG Leap Anti-Bac Mineral Pac. The ends of the pac will align with an L shaped key in the system. DO NOT FORCE.

KING TECHNOLOGY, INC.

530 11th Avenue South • Hopkins, MN 55343 • 952-933-6118 • FAX 952-933-2206 • www.kingtechnology.com



4. Replace cap on FROG Leap or POOL FROG System and set dial to **Setting 5**.



5. Turn on pump and allow 1 hour for the product to slowly dispense into the pool. If after 1 hour, the pac still contains some ingredient, re-insert, replace cap and run the circulation for an additional 30 minutes.



6. Remove the empty FROG Leap Depth Charge and discard or recycle.



7. Replace cap on FROG Leap or POOL FROG System and allow circulation to run at least 15 minutes before inserting any other FROG Leap products.

2. FROG Leap Reveille™



Dispense FROG Leap Reveille to establish your initial chlorine level in the pool following the same steps 1 through 7 for FROG Leap Depth Charge.

All components are recyclable when finished dispensing.

3. FROG Leap ALL-OUT™

Wait 24 hours after FROG Leap Depth Charge and FROG Leap Reveille to dispense FROG Leap ALL-OUT for a 90-day algae protection guarantee following steps 1-7 below:



1. Turn off pump and turn dial to Setting 0 and remove cap from the FROG Leap or POOL FROG System.



2. Remove cap from FROG Leap ALL-OUT without removing seal.

NOTE: Avoid adding other chemicals until this product has been circulated (filtered) for at least 24 hours.



3. Insert upside down into center of FROG Leap Anti-Bac Mineral Pac pushing down firmly on key to puncture seal.



4. Replace cap by hand only. **DO NOT OVER TIGHTEN**. Turn control dial to **Setting 5**.



5. Turn pump on for 90 minutes allowing FROG Leap ALL-OUT to circulate through pool.



6. To remove FROG Leap ALL-OUT, turn pump off, turn dial to 0, remove system cap.



7. Lift FROG Leap ALL-OUT up and allow any water in the container to drain through the system before recycling or discarding in trash.

NOTE: If water shows more than a hint of blue inside FROG Leap or POOL FROG System, replace the cap, turn dial to Setting 5 and run the pump for one minute.

7A. If pool size requires additional FROG Leap ALL-OUT, repeat steps 1-7.

After using FROG Leap Pool Wake Up!, insert your FROG Leap Torpedo Pac for continuous low-chlorine maintenance for weeks at a time.

U.S. Patent Numbers: D410,520; 6,210,566; 6,544,415; 6,814,095; 6,948,510 and other U.S. and Foreign patents pending.

553101143N 20-48-0260